

4ArXS HSD 150 W/70

4ArXS HSD | Long-life short-arc metal halide lamps



Areas of application

- Entertainment
- Archtainment

Product benefits

- Especially long lifespan



Product datasheet

Technical data


Electrical data

Nominal wattage	150 W
Nominal voltage	92.5 V
Nominal current	1.60 A

Light technical data

Nominal luminous flux	12000 lm
Luminous flux	12000 lm
Color temperature	7000 K

Dimensions & weight



Product line drawing

Diameter	20.0 mm
Length	105.0 mm

Lifespan

Lifespan	3000 h ¹⁾
----------	----------------------

¹⁾ Failure rate 2 % the first 3000 h. This statement must be restricted only to attributable lamp faults.

Additional product data

Base (standard designation)	G12
Footnote used only for product	Outer bulb with UV filter
Picto Studio	Yes

Capabilities

Product datasheet

Burning position	hs30
-------------------------	------

Certificates & standards

EEL – Energy Label	C
---------------------------	---


Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321202147	OSR4ARXSHSD15070	-	-	-

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, 4ArXS HSD lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.



Burning position

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321202147	4ArXS HSD 150 W/70	Folding carton box 1	51 mm x 46 mm x 143 mm	0.34 dm ³	61.00 g
4008321202154	4ArXS HSD 150 W/70	Shipping carton box 10	106 mm x 165 mm x 245 mm	4.29 dm ³	692.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Further information can be found in the following brochures, obtainable on request from OSRAM:

“Technology and applications of metal halide lamps”

“Guidelines for control gear and igniters for metal halide lamps”

“Availability of control gear and igniters”

“4ArXS has it all” – Innovative metal halide lamps for creative architecture and effect lighting

CD-ROM 4ArXS HSD

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.