

Application

Beam style	well-defined, flat field profile projection
Suitable for	theatres, TV studios, architectural and commercial applications, churches, exhibition and spot halls
Specification level	professional range
Beam angle	18°- 36° Typical throw distance 2 - 20m

Electrical specifications

Light source	230W LED, white
Supply Volts	100/260V AC single phase
Frequency / Current	50/60Hz – 1.17A @ 230V AC- 2,35 A @110V AC
Power consumption	250W at full power
Cable/connection	2m mains cable with fitted Neutrik powercon IN and OUT, supplied
Standards Compliance	EN60598-2-17, CE marked

Mechanical specifications

Construction	extruded aluminium and sheet steel
Mounting & suspension	steel stirrup 12mm centre hole + DIN mounting.
Handle	rear
Weight/Packed weight	17.1 kg / 19 kg
Colour frame	metal, 185 x 185mm, supplied

Operational specifications

Focus adjustment	slide zoom controls (dia. and softness) at side
Beam Shaping	4 shutters blades, supplied + iris diaphragm
DMX channels/connection	1 to 3 ch/ XLR5 connectors, IN/OUT
Colour	white, single source, no colour shift in fading
Dimming	manual, from rear panel or remote, 8 or 16 bits, via DMX
LED temperature	built-in sensor for real time monitoring
Ambient temperature	35°C max.
Fan speed control	3 modes available : Silent /Auto/ Constant
Fade curve / Built-in cue	2 curves(linear, square)
LED Frequency	16 KHz – Flicker free
LCD display	set up, dmX, monitor, diagnostics
RDM	integrated

Optical specifications

Optical system	double condenser with variable zoom
LED array	white, round-shaped, replaceable
Rated LED life	50,000 hours at 25°C, maintains 70% of original intensity
Beam colour temperature	3200K or 5600K
CRI (Colour Rendering Index)	>90

Accessories

Metal colour frame	■20100106 □20100106B ■20100106C
Iris diaphragm	20100707
Gobo holder, A/B metal	20100807 Gobo holder, B, dichro 20100807B
Hook clamp	20100900 Safety bond 20101300

Photometric data

Narrow focus		3200K								
Beam dia.	1.0	1.5	2.0	2.5	2.9	3.4	3.9	4.4	4.9	m
lux	12938	5750	3234	2070	1438	1056	809	639	518	
Distance	4	6	8	10	12	14	16	18	20	m

Wide focus										
Beam dia.	3.8	4.4	5.0	5.7	6.3	7.6	8.2	8.8	9.5	m
lux	1528	1122	859	679	550	382	325	281	215	
Distance	6	7	8	9	10	12	13	14	16	m

Narrow focus		5600K								
Beam dia.	1.0	1.5	2.0	2.5	2.9	3.4	3.9	4.4	4.9	m
Lux	20938	9306	5234	3350	2326	1709	1309	1034	838	
Distance	4	6	8	10	12	14	16	18	20	m


Wide focus										
Beam dia.	3.8	4.4	5.0	5.7	6.3	7.6	8.2	8.8	9.5	m
lux	2500	1837	1406	1111	900	625	533	459	352	
Distance	6	7	8	9	10	12	13	14	16	m

LUCI DELLA RIBALTA PROFESSIONAL LIGHTING PRODUCTS

alba 18/36

230W, 100/260VAC DMX512+RDM
wide angle led profile


part # ■ 01204030 □ 01204031 ■ 01204032 3200K
part # ■ 01204130 □ 01204131 ■ 01204132 5600K



Stylish, compact and extremely high efficiency wide angle LED zoom profile featuring a white led COB power source and double-condenser optics. Alba is DMX/RDM controllable for 16 bit dimming.

Ideal in all applications where heat and energy saving are a concern. Its extremely accurate optics make it the obvious choice in theatrical sets, TV studios, commercial displays and architectural applications where an excellent optical performance is required. Standard delivery includes 1.5m mains cable with fitted Power-con, 4 shutter blades and a metal colour frame.

All models in the Alba range are available in 3200K and 5600K white, RGBW and TW, in a choice of 3 finishes: black, white and silver, and 2 stirrups: manual and pole-operated



Luci della Ribalta srl
Via Berna 14
46042 Castel Goffredo (MN), Italy
tel: +39 0376 771777
www.ldr.it info@ldr.it

issue: ap ©2020. LDR reserves the right to alter the specification without prior notice.