



## FUZE PAR Z60 IP™

SKU# FUZ001

The IP65 rated FUZE PAR Z60 IP™ is a single source silent operating par luminaire with a 60W Quad Color RGBW COB LED. Features 7° to 39° motorized zoom, RGBW color mixing, electronic strobe and selectable dimming curve effects, DMX and RDM (remote device management) protocol support, IP rated 5pin XLR and IP65 Locking Power in/out connections, LCD menu display with 4 touch button control panel, dual adjustable yokes, multiple unit power linking, flicker free operation for TV and FILM, a multi-voltage universal auto switching power supply (110-240v), and removable gel frame and barn doors included.



### FEATURES

**IP65 Rated**

**60W RGBW COB LED Par Luminaire**

**7° to 39° Motorized Zoom Range**

**Silent Operation**

**RGBW Color Mixing**

**Dual Adjustable Yokes**

**Multiple Unit Power Linking**

**Flicker Free Operation for Broadcast TV and FILM**

**Removable Gel Frame and Barn Doors Included**



ELATION | FUZE PAR Z60 IP™ | Product Specification Sheet

**PRODUCT SPECIFICATIONS**

**SOURCE**

60W RGBW COB LED  
100,000 Hour Average LED Life\*

\*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

**PHOTOMETRIC DATA**

3,813 LUX 354 FC @9.8' (3m) (7° Full ON)  
228 LUX 21 FC @9.8' (3m) (39° Full ON)

**EFFECTS**

RGBW Color Mixing  
7° - 39° Beam Zoom Range  
Electronic Strobe and Dimming  
Variable Dimming Curves  
64 Color Presets and 14 Unique Color Macros

**COLOR**

RGBW

**CONTROL / CONNECTIONS**

(12) DMX Channel Modes (13 Total Channels)  
RDM (Remote Device Management)  
(4) Button TouchControl Panel  
IP Rated 5pin DMX In/Out  
IP65 Locking Power Connector In/Out

**SIZE / WEIGHT**

Length: 10.0" (253mm)  
Width: 9.9" (252mm)  
Vertical Height: 11.1" (282mm)  
Weight: 10 lbs. (4.5 kg)

**ELECTRICAL / THERMAL**

AC 110-240V - 50/60Hz  
78W Max Power Consumption  
Multiple Unit Power Linking  
5°F to 113°F (-15°C to 45°C)

**INCLUDED ITEMS**

IP65 Power Locking Connector In/Out  
Gel Frame  
Barn Door

**APPROVALS / RATINGS**



**OPTIONAL ACCESSORIES**

ORDER CODE	ITEM
NARROW CLAMP	PRO 2" Wrap Around Clamp
NEU088	3 ft. (1m) IP65 Power Link Cable
	Additional cable lengths available

**PHOTOMETRIC DATA**


**MIN ZOOM - 7° Beam Diameter**

	3 m	9.8 ft	4 m	13.1 ft	5 m	16.4 ft
7° Beam Diameter	0.3	1.0	0.39	1.3	0.47	1.5
12° Field Diameter	0.56	1.8	0.74	2.4	0.91	3.0
	lux	fc	lux	fc	lux	fc
RED LEDs	833	77	523	49	347	32
GREEN LEDs	1,182	110	717	67	432	40
BLUE LEDs	316	29	188	17	122	11
WHITE LEDs	1,762	164	1,068	99	721	67
FULL ON	3,813	354	2,321	216	1,538	143

**MAX ZOOM - 39° Beam Diameter**

	3 m	9.8 ft	4 m	13.1 ft	5 m	16.4 ft
39° Beam Diameter	2.16	7.1	2.89	9.5	3.61	11.8
43° Field Diameter	2.45	8.0	3.27	10.7	4.1	13.5
	lux	fc	lux	fc	lux	fc
RED LEDs	60	6	36	3	25	2
GREEN LEDs	75	7	44	4	31	3
BLUE LEDs	24	2	15	1	12	1
WHITE LEDs	107	10	64	6	44	4
FULL ON	228	21	135	13	88	8

**DIMENSIONAL DIAGRAMS**



Specifications are subject to change without notice ©Elation Professional 08/05/16

