

TEMPO F 650 PLUS

LDR
LUCI DELLA RIBALTA

10601000 black

10601001 white

10601002 silver



PRODUCT SPECS

lens type
120mm dia. Fresnel

reflector
55mm dia. glass

microswitch
no

colour frame
150x150mm

throw
2-10m

beam angle
7°-60°

weight
4 kg

Quality yet budget-priced 500W or 650W Fresnel spotlight. It features a slide-focus variable-spread, soft edged beam which makes it ideal for small, intimate stage areas.

Also included as standard are a DIN standard colour frame, safety guard and 1,5m mains cable. Available to special order in any colour from the RAL range.

Illuminatore fresnel da 500/650W di elevato livello qualitativo e tuttavia di gamma economica.

Produce un fascio di luce regolabile molto morbido e soffuso, che lo rende ideale per l'utilizzo in scene di piccole dimensioni. Fornito di serie completo di telaio portagelatina, rete di protezione e 1,5m cavo di alimentazione.

ACCESSORIES

- 20100103 colour frame, black
- 20100103B colour frame, white
- 20100103C colour frame, silver
- 20100303 4-leaf barndoor, black
- 20100303B 4-leaf barndoor, white
- 20100303C 4-leaf barndoor, silver
- 20100303D 4-leaf barndoor, white/black
- 20100303E 4-leaf barndoor, silver/black
- 20100900 hook clamp
- 20101300 safety bond
- 20106013 colour scroller Xpress 13
- 20600003 plate 150x150mm for Xpress13

COMPATIBLE LAMPS

M38	GY9.5	300W	230V/240V	2950K	2000 hrs
M40	GY9.5	500W	230V/240V	2950K	2000 hrs
T18	GY9.5	500W	230V/240V	3000K	360 hrs
T25	GY9.5	500W	230V/240V	3000K	360 hrs
T26	GY9.5	650W	230V/240V	3050K	600 hrs
T27	GY9.5	650W	230V/240V	3050K	600 hrs

LDR recommends Philips lamps

PHOTOMETRIC DATA T27

	SPOT									
m Ø	0,2	0,4	0,5	0,6	0,7	0,9	1,0	1,1	1,2	
lux	16.600	7.378	4.150	2.656	1.844	1.355	1.038	820	664	
m	2	3	4	5	6	7	8	9	10	
	FLOOD									
m Ø	2,3	3,5	4,6	5,8	6,9	8,1	9,2	10,4	11,5	
lux	3.096	1.376	774	495	344	253	194	153	124	
m	2	3	4	5	6	7	8	9	10	

